HIGH DENSITY YELLOW GAS LINE TAPE (1.0 density)



APPLICATION

This specification applies to expanded, 0.9 density x .004 Yellow PTFE Thread Seal Tape supplied on finished spools.

SUPER DOAR

COMPOSITION

Min. 99% virgin PTFE, Max. 1% Pigment

GENERAL APPEARANCE

The tape appears pale yellow in color. It shall be free of visible voids, cracks, folds, contamination and have consistent physical properties.

PHYSICAL PROPERTIES:

| Technical Performance: | Tolerance | Method | Units | |
|------------------------|------------------|-----------------|-------------------|--|
| Width | +.03125 | N/A | Inches | |
| Length | 260" / 520" | N/A | Inches | |
| Thickness | .0040 + .0005/-0 | ASTM D374-42-A | Inches | |
| Density | 0.9 | ASTM D792 | g/cm ³ | |
| Tensile-Longitudinal | 3,000 max. | ASTM D882 (mod) | PSI | |
| Elongation | 50% min. | ASTM D882 (mod) | % | |

PACKAGING

The 1.0 density expanded PTFE Thread Seal Tapes are wound in 1 inch 1D plastic spools unless otherwise specified. Bulk packaging is sufficient to prevent damage during shipment.

USEFUL TEMPERATURE RANGE: -450°F to +500°F

REACTIVITY: Chemically inert to virtually all environments

FLAMMABILITY: Non-Flammable

STORAGE: Unlimited shelf-life (Less than 70° recommended).

Capable of sealing all liquids and gases. Oxygen is the only exception.

ARGCO ITEM NUMBERS:

6010170: 1/2" x 260" 6010171: 1/2" x 520" 6010173: 3/4" x 520" 6010174: 1" x 260"

| System No. | Location | Spec Section | Paragraph | |
|--------------|----------|--------------|-----------|--|
| Submitted By | Date | Approved | Date | |

